

IN11086PN INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions as you may need them a later date.

CAUTION

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustration.

ASSEMBLY AND INSTALLATION

1. Screw nipple into coupling with hex nut, attach tube and tube cover onto the nipple, then screw loop onto the nipple.
2. Use two quick links to attach the chain to loops.
3. Attach the cross bar to the outlet box with the 2 mounting screws.
4. Lower the canopy onto the top nut and pass the top loop through canopy.
5. Attach the nipple to the cross bar with washer and hex nut.
6. Attach top loop to the nipple.
7. Make wire connections:
 - The ridged wire (unmarked) from the fixture to white wire from power source.
 - The smooth wire (marked) from the fixture to black wire from power source.
 - Loop the ground wire to cross bar with a ground screw.
8. Place the canopy over the outlet box and secure the canopy with top nut.
9. Install bulbs: (bulbs not included). (Don't exceed the maximum capacity recommended on the sockets).
10. Screw the rod into the coupling with hex nut, then attach diffuser, rubber washer and metal washer to the metal frame. Secure with the hex nut.
11. Attach bottom cover and secure with finial.
12. Attach the crystal drops (total 72pcs) to the metal frame. (See fig.)

1500 Cherokee Parkway, Suite 100, Acworth, GA 30102
Phone: (866) 845-5451 • Fax: (866) 816-6165
E: service@acclaim-lighting.com • www.acclaim-lighting.com

ACCLAIM
LIGHTING
INTERIOR • OUTDOOR

