

# IN21149ORB

## INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions, as you may need them at a later date.

### CAUTION

**WARNING:** Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor. Min 90°C supply conductors.

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

### GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

### ASSEMBLY AND INSTALLATION

- Carefully unpack and lay out the parts as shown in illustration and read all instructions before starting.
- Rod Connections:
  - Thread the fixture wire from the lamp body (16) through the lower stem (15), and then secure the lower stem (15) on to lamp body (16) using the nipple (13).
  - Thread the fixture wire through the middle stem (14), and then secure the middle stem (14) on to the lower stem (15) using the nipple (13).
  - Thread the fixture wire through the upper stem (12), and then secure the upper stem (12) on to the middle stem (14) using the nipple (13).
- Thread the fixture wire through the swivel (11) and canopy (9), and then secure the stem assembly to the swivel (11) of the canopy.
- Attach the cross bar (7) to the outlet box by using two box screws (8).
  - Ribbed wire (w/o marking) from light to White wire (2) from power source
  - Smooth wire (w/o marking) from light to Black wire (3) from power source
  - Loop the ground wire (4) to cross bar (7) with a ground screw (6)
- Attach the canopy (9) to the cross bar (7) by inserting the fixture mounting screws, and then secure it with two ball nuts (10).
- Attach the metal frame (18) to the hole of socket cup (17), and turn counterclockwise until the frame is secure.
- Screw the bulb (not included) into the socket ring.
- Angled mounting recommended for a vaulted or angled ceiling. (See Fig. 1)

